



DrainWatch is a durable and reliable dosing system suitable for indoor and outdoor applications that require the delivery of a single chemical at timed intervals.

Available as a mains or battery operated system, DrainWatch is commonly used for drain and grease trap maintenance and other purposes such as water treatment applications.



## **Key Features**

- Rated IP65 for indoor and outdoor use in tough industrial environments
- Long-life premium motor for extended running life
- Multi-lingual programming with quick access review of events from one single screen
- LCD digital interface with character display and backlight for ease-of-use
- Optional access code protection to prevent unauthorised use
- Easily serviced from the front with compression connectors to facilitate quick tube changes
- Efficient and fast installation with mounting bracket and spirit level
- · Low battery indicator as standard for battery models
- · On/Off LED indicator



Mains Operated DrainWatch





## **Battery Operated DrainWatch**

Rated IP65, this battery operated system offers great flexibility as it can be installed outdoors or in any setting where power outlets are not readily accessible. Additionally, the modular design allows for the battery pack to be mounted on the left or right side of the unit making it the ideal solution for tight-fitting installations.

DrainWatch runs on 4 x D Cell batteries with a built-in low battery light indicator that alerts users when the batteries need to be replaced.



**Battery Operated DrainWatch** 

## Why choose DrainWatch?

DrainWatch is one of the most robust, dosing systems available on the market. A premium product without the added cost, DrainWatch has been designed with high quality, UL approved polypropylene plastic. The front cover offers enhanced durability with protective corner bumpers and a tough rubber control panel.

As with all Brightwell Dispensers' products, design is paramount. The modern, contemporary styling not only offers cleaning and aesthetic benefits to end-users, but it also provides a range of practical advantages for installers in terms of simple set-up and flexible programming and mounting options.

DRAINWATCH SPECIFICATIONS							
	Power Supply	Motor	No. of Feeds/ 24 hrs	Flow Rate*	Pump	Installation Kit	Approvals**
Mains Operated	100 - 240V AC	DC Brushed Motor	20	100ml/m	Peristaltic Pump/ Silicone Tube	Drain Pipe Injector Cable Tie PVC tube Weight Foot Filter	CE Class 2 Product Certification IP65 Rated
Battery Operated	4 x D Cell			100ml/m			
*Flow rates are approximate and subject to environmental conditions **Pending							

Distributed by:



revolutionary dispensing solutions

Head Office: Brightwell Dispensers Ltd **Brightwell Industrial Estate** Norton Road, Newhaven East Sussex, BN9 0JF UK

Tel: +44 (0)1273 513566 Fax: +44 (0)1273 516134

sales@brightwell.co.uk www.briahtwell.co.uk