



MOBILE MAIN STATION **VOYAGER**

The mobile cleaning unit, Voyager, can be used to cover large areas, generally with a considerable degree of flexibility.

Voyager enables rinsing, foam application and disinfection to be performed.

HIGHLIGHTS

- Stand-alone mobile cleaning unit
- Can be used for rinsing, application of foam and disinfection
- Option outlet for rinsing outlet or separate foam or disinfectant injector outlet

VARIANTS

Voyager is available in three different capacities and with or without a built-in compressor.

TECHNICAL SPECIFICATIONS

MODEL	1	1K	2	2K	4	4K
Number of users	1	1	1	1	1	1
Pump	CMV 3-8 X	CMV 3-8 X	CRNE 3-9 J	CRNE 3-9 J	CRNE 3-9 J	CRNE 3-9 J
Motor, output	1.1 kW 1.5 HP	1.1 kW 1.5 HP	2.2 kW 3.0 HP	2.2 kW 3.0 HP	4.0 kW 5.4 HP	4.0 kW 5.4 HP
OUTLET HOSE						
Max. outlet hose length	20 metres	20 metres	35 metres	35 metres	35 metres	35 metres
DIMENSIONS						
Height	970 mm	970 mm	970 mm	970 mm	970 mm	970 mm
Length	1350 mm	1350 mm	1350 mm	1350 mm	1350 mm	1350 mm
Width	570 mm	570 mm	570 mm	570 mm	570 mm	570 mm
Weight	70 kg	90 kg	100 kg	120 kg	120 kg	140 kg

Please note : Requirements when units are running:

ELECTRICAL SUPPLY

Current 1x230V/50Hz	5.0 amp	5.0 amp	-	-	-	-
Current 3x230V/50Hz	-	-	8.0 amp	8.0 amp	13.0 amp	13.0 amp
Current 3x400V/50Hz	-	-	5.0 amp	5.0 amp	9.0 amp	9.0 amp

WATER SUPPLY

Connection, inlet water**	¾"	¾"	¾"	¾"	¾"	¾"
Connection, outlet water	½"	½"	½"	½"	½"	½"
Max. water temperature	70° C	70° C	70° C	70° C	70° C	70° C
Min. water inlet flow	3.0 m³/h	3.0 m³/h	4.5 m³/h	4.5 m³/h	4.5 m³/h	4.5 m³/h
Min. inlet water pressure	1.5 bar	1.5 bar	1.5 bar	1.5 bar	1.5 bar	1.5 bar
Max. inlet water pressure	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar
Water pressure at 30 l/m*	10 bar	10 bar	-	-	-	-
Pump pressure at 40 l/min*	-	-	20 bar	20 bar	25 bar	25 bar

AIR SUPPLY

Compressor	-	Oilless	-	Oilless	-	Oilless
Minimum air pressure	5 bar	-	5 bar	-	5 bar	-
Maximum air pressure	10 bar	-	10 bar	-	10 bar	-
Minimum air supply flow	150 l/min	-	150 l/min	-	150 l/min	-

* At a 4 bar inlet pressure

** Option with extra outlet: Requires connection hose 1" (Voyager 4/4K)

SYSTEM CONFIGURATION

CHOOSE VARIANT

Voyager 1	(1x230V/50Hz)	201-201010	Voyager 4	(3x230V/50Hz)	201-204000
Voyager 1K	(1x230V/50Hz)	201-201040	Voyager 4	(3x400V/50Hz)	201-204020
Voyager 2	(3x230V/50Hz)	201-202000	Voyager 4K	(3x230V/50Hz)	201-204040
Voyager 2	(3x400V/50Hz)	201-202020	Voyager 4K	(3x400V/50Hz)	201-204060
Voyager 2K	(3x230V/50Hz)	201-202040			
Voyager 2K	(3x400V/50Hz)	201-202060			